


Simple, Reliable and Accurate

- Completely Automatic Operation
- Easy Adjustment and Maintenance
- Quality Approved Materials
- World Wide Support

CLA-VAL SERIES 81 Main Function



▶ CLA-VAL 81-01 Typical Application

The CLA-VAL 81-01 is designed to be used when a positive shut-off is required.

The CLA-VAL 81-01 is typically installed on the discharge of pumps or well pumping systems to prevent backflow when the pump is off.

Installation: Reverse Flow



The CLA-VAL SERIES 81 is a hydraulically operated Check Valve. The valve opens when inlet pressure exceeds outlet pressure. In case of reversal pressure, the higher outlet pressure closes the valve to prevent backflow through the valve.

Make your Valve even Better!

LFS Option? Control Low flows or night flows KO Option? Extend valve life with Anti-Cavitation trim KG1 Option? Use stem cleaning for harsh water Maintenance? Check on periodic maintenance Environment? Adapt to high temperatures or frost risk Security? Add hydraulic safety back-up to your valve Protection? Remove excessive system overpressures Corrosion? Protect your valve with upgraded materials Not just Products but Solutions: contact CLA-VAL!



► CLA-VAL UK Limited www.cla-val.co.uk info@cla-val.co.uk 1 - 081001DE C 11/18